

Easy programming using selection button sequence

Electronic control and data-recording

Energy management by real time clock

Electronically controlled forced air-cooling

Each column has individual vend motor

24 V D/C motors

Interchangeable parts



## Model

## VDI 476-7

|                          |        |
|--------------------------|--------|
| Selections / Columns     | 10 / 7 |
| Max. product length (mm) | 505    |
| Max. product Ø (mm)      | 72     |

### Capacities:

|            |        |     |
|------------|--------|-----|
| Can        | 0,33 l | 476 |
| PET bottle | 0,50 l | 238 |

### Dimensions and weights:

|                |                  |
|----------------|------------------|
| H x W x D (mm) | 1830 x 750 x 940 |
| Weight         | 310 kg           |

### Performance data:

|                        |               |
|------------------------|---------------|
| Refrigeration          | 0,997 kW      |
| Power supply           | 230 V / 50 Hz |
| Max. power consumption | 875 W         |

|         |                                      |
|---------|--------------------------------------|
| Control | Executive; MDB                       |
| Cabinet | Zinc coated steel,<br>powder painted |

### Standard:

Black cabinet  
5 digit display  
Safety coin return  
Anti-vandalism panel in  
selection button area  
Cut out for validator or  
alternative payment system  
Lock  
Choice of neutral front poster

### Options:

Cabinet colour on request  
Two-line LCD display  
Security cash system  
Safety sliding coin insert  
Anti-rain kit IP 34  
Loading rack  
DEX / UCS interface  
Special coded lock  
Individual graphics